

INDUSTRIAL COMPONENT DATA

PTI 16/S 3214029 PHOENIX CONTACT Installation terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTI 16/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTI 16/S
Catalog number	3214029
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-A7463DDBF1
Generated	2026-08-02

Product Overview

Installation terminal block

Terminal block, nominal voltage: 500 V, nominal current: 76 A, Push-in connection, 1st floor, Dimensioning cross-section: 16 mm², cross-section: 0.5 mm² - 16 mm², installation class: NS 35/7.5, NS 35/15, colour: grey

Installation terminal block, nom. voltage: 500 V, nominal current: 76 A, Push-in connection, 1 level, Rated cross section: 16 mm², cross section: 0.5 mm² - 16 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataProduct propertiesProduct type Installation terminal block

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 01

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 6 kV

Maximum power dissipation for nominal condition 2.43 W

Connection dataPEN function yes

Number of connections per level 2

Nominal cross section 16 mm²

1 level

Stripping length 18 mm

Internal cylindrical gage A6

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.5 mm² ... 16 mm²

Cross section AWG 24 ... 6 (converted acc. to IEC)

Conductor cross section flexible 0.5 mm² ... 16 mm²

Conductor cross section, flexible [AWG] 20 ... 6 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 16 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.5 mm² ... 16 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 1.5 mm² ... 4 mm²

Nominal current 76 A

Maximum load current 76 A (with 16 mm² conductor cross section)

Nominal voltage 500 V

Nominal cross section 16 mm²

1 level Connection cross sections directly pluggable

Conductor cross section rigid 1 mm² ... 16 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 4 mm² ... 16 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 2.5 mm² ... 16 mm²

DimensionsWidth 10.2 mm

End cover width 2.2 mm

Heig...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTI 16/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.