

INDUSTRIAL COMPONENT DATA

PTIO 1,5/S/4-PE-LED 24 GN 3244466 PHOENIX CONTACT

Sensor/actuator terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTIO 1,5/S/4-PE-LED 24 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTIO 1,5/S/4-PE-LED 24 GN
Catalog number	3244466
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-3D58D7195A
Generated	2026-08-06

Product Overview

Sensor/actuator terminal block

Terminal block for detectors/actuators, with green light indication and grounding conductor function, nominal voltage: 24 V, nominal current: 13.5 A, number of connections: 5, connection type: Push-in connection, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

Initiator/actuator terminal block, with green LED display and protective conductor function, nom. voltage: 24 V, nominal current: 13.5 A, number of connections: 5, connection method: Push-in connection, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 1.5 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator terminal block

Number of connections 5

Number of rows 4

Potentials 4

Data management status

Article revision 02

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 4 kV
LED voltage range 15 V AC/DC ... 30 V AC/DC
LED current range 0.31 mA ... 0.95 mA
Input data LED voltage range 15 V AC/DC ... 30 V AC/DC
Connection data Grounding foot Yes
Number of connections per level 2
Nominal cross section 1.5 mm²
Rated cross section AWG 14
Note Please observe the current carrying capacity of the DIN rails.
Stripping length 8 mm
Internal cylindrical gage A1 / B1
Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Cross section AWG 26 ... 16 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] 26 ... 16 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1 mm² Using the AI-S 1-8 TQ ferrule, Item No. 1200293, is recommended
Nominal current 13.5 A
Maximum load current 13.5 A
Nominal voltage 24 V
Nominal cross section 1.5 mm²
Connection cross sections directly pluggable
Conductor cross section rigid 0.25 mm² ... 1.5 mm²
Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 1.5 mm²
Flexible co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTIO 1,5/S/4-PE-LED 24 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.