

**INDUSTRIAL COMPONENT DATA**

# PTMC 1,5/32-2H VDE0815 19Z A-H 3270393 PHOENIX CONTACT Marshalling patchboard

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTMC 1,5/32-2H VDE0815 19Z A-H



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | PTMC 1,5/32-2H VDE0815 19Z A-H |
| Catalog number  | 3270393                        |
| Category        | Feed-through terminal block    |
| Minimum order   | 24 Pcs                         |
| Document ID     | EO-198D8CCC3B                  |
| Generated       | 2026-08-04                     |

## Product Overview

Marshalling patchboard

Marshalling array, A-H labeling, rated voltage: 500 V, rated current: 17.5 A, connection type: Push-in connection, cross-section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting: Wall mounting, 19" rack, color: gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Enclosures connectivity

## Additional Product Information

Key Commercial Data

Orderkey 3270393

Packing unit 24 pc

Note Made to Order (non-returnable)

Catalog page Page 63 (C-1-2017)

GTIN 4055626324494

Weight per Piece (excluding packing) 112.290 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Marked A - H

Number of positions 32

Number of levels 1

Number of connections 128  
Nominal cross section 1.5 mm<sup>2</sup>  
Color gray  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 0.56 W (the value is based on one connection block and is multiplied according to the pin assignment)  
Maximum load current 24 A (in case of a 2.5 mm<sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)  
12 A (in case of a 2.5 mm<sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)  
Nominal current I<sub>N</sub> 17.5 A  
Nominal voltage U<sub>N</sub> 500 V  
Open side panel No  
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Result of surge voltage test Test passed  
Surge voltage test setpoint 7.3 kV  
Result of power-frequency withstand voltage test Test passed  
Power frequency withstand voltage setpoint 1.89 kV  
Result of the test for mechanical stability of terminal points (5 x conductor conn...)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTMC 1,5/32-2H VDE0815 19Z A-H with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.