


INDUSTRIAL COMPONENT DATA

PTME 4 WH 3212140 PHOENIX CONTACT Test disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTME 4 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTME 4 WH
Catalog number	3212140
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-2D13ECDDD8
Generated	2026-08-05

Product Overview

Test disconnect terminal block

Borne interrupts. for circ. measurement, nominal voltage: 500 V, nominal current: 24 A, number of connections: 2, connection type: Push-in connection, 1st floor, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: white

Test Shut-Off Terminal Block, Nominal Voltage: 500 V, Rated Current: 24 A, Number of Connections: 2, Connection Type: Push-in Connection, 1st Stage, Reference Section: 4 mm², Cross-Section: 0.2 mm² - 6 mm², Installation Type: NS 35/7.5, NS 35/15, Colour: White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3212140

Packing unit 50 pc

GTIN 4046356681834

Weight per Piece (excluding packing) 14.130 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 4 mm²

Color white

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Maximum load current 24 A

Nominal current I_N 24 A

Nominal voltage U_N 500 V

Open side panel Yes

Dimensions

Width 6.2 mm

End cover width 2.2 mm

Length 70.5 mm

Height 48.8 mm

Height NS 35/7,5 49.5 mm

Height NS 35/15 57 mm

Connection data

Connection method Push-in connection

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

2 conductors with same cross sectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTME 4 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.