

INDUSTRIAL COMPONENT DATA

PTPOWER 185-3L 1054728 PHOENIX CONTACT Terminal current, locked, voltage rating: 1500 VA DC / 1000 V AC, rat..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 185-3L



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTPOWER 185-3L
Catalog number	1054728
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-6CAF88FCA9
Generated	2026-08-04

Product Overview

Terminal current, locked, voltage rating: 1500 VA DC / 1000 V AC, rated current: 309 A, type of Connection: Connection to Power Turn, number of connections: 6, number of poles: 3, section: 95 mm²-185 mm², AWG: 3/0-350 kcmil, width: 93 mm, color: gray, assembly type: NS 35/15

Power terminal, locked, nominal voltage: 1000 V, nominal current: 309 A, connection type: Power Turn connection, 1st floor, cross-section: 95 mm² - 185 mm², mounting type: NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPOWER 185-3L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.