

INDUSTRIAL COMPONENT DATA

PTRV 4 /GY 3270117 PHOENIX CONTACT Marshalling panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTRV 4 /GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTRV 4 /GY
Catalog number	3270117
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-6CA88A919D
Generated	2026-07-29

Product Overview

Marshalling panel

Switching distributor, nominal voltage: 250 V, nominal current: 10 A, connection type: Push-in connection, 1., 2., 3. and 4th floor, Dimensioning section: 1.5 mm², cross-section: 0.14 mm² - 2.5 mm², mounting: NS 35/7.5, NS 35/15, colour: grey, connection element colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3270117

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4055626435176

Weight per Piece (excluding packing) 17.400 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 2

Number of levels 4

Number of connections 16

Potentials 4

Nominal cross section 1.5 mm²
Color gray
Color of connection elements gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)
Maximum load current 10 A (with 1.5 mm² conductor cross section)
Nominal current I_N 10 A
Nominal voltage U_N 250 V
Open side panel Yes
Dimensions
Width 8.3 mm
Length 64 mm
Height NS 35/7,5 55.5 mm
Height NS 35/15 63 mm
Connection data
Connection method Push-in connection
Stripping length 8 mm ... 10 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross section, flexible 14
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTRV 4 /GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.