

INDUSTRIAL COMPONENT DATA

PTRV 4 /SENSOR 4POL 1162613 PHOENIX CONTACT

Switching distributor, nominal voltage: 250 V, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTRV 4 /SENSOR 4POL



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTRV 4 /SENSOR 4POL
Catalog number	1162613
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-2A8925CA7B
Generated	2026-08-04

Product Overview

Switching distributor, nominal voltage: 250 V, nominal current: 10 A, connection type: Push-in connection, 1., 2., 3. and 4th floor, Sizing section: 1.5 mm², cross-section: 0.14 mm² - 2.5 mm², mounting: NS 35/7.5, NS 35/15, color: gray, connection elements color: multicolor

Manoeuvring distributor, rated voltage: 250 V, rated current: 10 A, section: 0.14 mm² - 2.5 mm², AWG: 14 - 26, connection type: Push-in connection, number of poles: 2, number of connections: 16, width: 8.3 mm, length: 64 mm, colour: grey, colour connecting elements: white, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

ETIM for 1162613 Terminal blocks (EC000897)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²
Rated current I_n (EF008250)
10 A
Rated voltage (EF000228)
250 V
Type of electrical connection 1 (EF002526)
Other
Type of electrical connection 2 (EF002527)
Other
Number of levels (EF002659)
4
Number of clamp positions per level (EF002660)
4
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
8.3 mm
Height (EF000040)
64 mm
Depth (EF000049)
55.5 mm
Closing plate required (EF002525)
Yes
Colour (EF000007)
Grey
Internally connected stages (EF002661)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTRV 4 / SENSOR 4POL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.