

INDUSTRIAL COMPONENT DATA

PTRV 8 /BK 1061722 PHOENIX CONTACT Rangierverteiler

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTRV 8 /BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTRV 8 /BK
Catalog number	1061722
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-AE86F3397E
Generated	2026-07-27

Product Overview

Rangierverteiler

Switching distributor, nominal voltage: 250 V, nominal current: 8 A, connection type: Push-in connection, 1., 2., 3., 4., 5., 6., 7. and 8th floor, Sizing section: 1.5 mm², cross-section: 0.14 mm² - 2.5 mm², mounting: NS 35/7.5, NS 35/15, color: gray, connection elements color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 1061722

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4055626716824

Weight per Piece (excluding packing) 33.780 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 2

Number of levels 8

Number of connections 32

Potentials 8

Nominal cross section 1.5 mm²

Color gray

Color of connection elements black

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)

Maximum load current 8 A (with 1.5 mm² conductor cross section)

Nominal current I_N 8 A

Nominal voltage U_N 250 V

Open side panel Yes

Dimensions

Width 8.3 mm

Length 100 mm

Height NS 35/7,5 87.5 mm

Height NS 35/15 95 mm

Connection data

Connection method Push-in connection

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Min. AWG conductor cross section, flexible 26

Max. AWG conductor cross section, flexible 14

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with fer...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTRV 8 /BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.