


INDUSTRIAL COMPONENT DATA

PTS 1,5/ 2-5,0-H BK/YE 1703901 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 1,5/ 2-5,0-H BK/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTS 1,5/ 2-5,0-H BK/YE
Catalog number	1703901
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-3EA9CEF32A
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 16 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, family of articles: PTS 1.5/.. -H, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: multicolor, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.5 mm, packaging type: boxed

Printed circuit board terminal, nominal current: 16 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: PTS 1.5/.. -H, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1703901

Packing unit 1

GTIN 4046356917445

Custom tariff number 85369010

Dimensions

Length [L] 10.5 mm

Pitch 5 mm

Dimension a 5 mm

Width [w] 10 mm

Height 13.6 mm

Height [h] 16.1 mm

Solder pin [P] 2.5 mm

Hole diameter 1.2 mm

General

Range of articles PTS 1,5/..-H

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Nominal current IN 16 A

Nominal cross section 1.5 mm²

Solder pin surface

Stripping length 8 mm

Number of positions 2

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss 7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 1,5/ 2-5,0-H BK/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.