

INDUSTRIAL COMPONENT DATA

PTS 1,5/ 3-PH-5,0 BK 1705165 PHOENIX CONTACT Plug-in part, rated current: 10 A, number of poles: 3, pitch: 5..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 1,5/ 3-PH-5,0 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTS 1,5/ 3-PH-5,0 BK
Catalog number	1705165
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-3FD15B444A
Generated	2026-08-05

Product Overview

Plug-in part, rated current: 10 A, number of poles: 3, pitch: 5 mm, connection type: Push-in spring connection, color: black, contact surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 10 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: PTS 1.5/.. -PH, pitch: 5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Plug component, nominal current: 10 A, number of positions: 3, pitch: 5 mm, connection method: Push-in spring connection, color: black, contact surface: Tin

Your advantages

Time saving push-in connection, tools not required
Defined contact force ensures that contact remains stable over the long term
Intuitive use through colour coded actuation lever
Quick and convenient testing using integrated test option
Largest possible clamping space in a small component size

Key Commercial Data

Orderkey 1705165

Packing unit 1

GTIN 4046356756112

Custom tariff number 85366990

General

Range of articles PTS 1,5/..-PH

Type of contact Female connector

Number of positions 3

Connection method Push-in spring connection

Rated voltage (III/3) 250 V

Nominal current I_N 10 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 1,5/ 3-PH-5,0 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.