

INDUSTRIAL COMPONENT DATA

PTSA 1,5/13-3,5-F BUGY 1700763 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 1,5/13-3,5-F BUGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSA 1,5/13-3,5-F BUGY
Catalog number	1700763
Category	Printed circuit board terminal
Minimum order	60 Pcs
Document ID	EO-92B2363F11
Generated	2026-08-05

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 8 A, nominal voltage (III/2): 250 V, nominal cross-section: 1.5 mm², number of potentials: 13, number of rows: 1, number of poles per row: 13, article family: PTSA 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: bluish gray, Pin arrangement: Linear front pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1700763

Packing unit 1

GTIN 4046356499842

Custom tariff number 85369010

Dimensions

Length [l] 12 mm

Pitch 3.5 mm

Dimension a 42 mm

Width [w] 47 mm

Height 13.1 mm

Height [h] 16.7 mm

Solder pin [P] 3.6 mm

Pin spacing 3.5 mm

Hole diameter 1 mm

General

Range of articles PTSA 1,5

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 200 V

Rated voltage (III/2) 250 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Solder pin surface

Stripping length 9 mm

Number of positions 13

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141111eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121432

ETIM for 1700763 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

16.7 mm

Number of electrical connections (EF008252)

13

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

3.5 mm

R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 1,5/13-3,5-F BUGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.