

INDUSTRIAL COMPONENT DATA

PTS 2,5-QUATTRO BK 1094477 PHOENIX CONTACT Terminal step, nominal voltage: 800 V, nominal current: 24 A, typ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 2,5-QUATTRO BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTS 2,5-QUATTRO BK
Catalog number	1094477
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-F33DA5E285
Generated	2026-08-02

Product Overview

Terminal step, nominal voltage: 800 V, nominal current: 24 A, type of connection: Connection push-in connection, number of connections: 4, section: 0.14 mm² - 4 mm², AWG: 26 - 12, width: 5,2 mm, color: black, type of mounting: NS 35/7,5, NS 35/15

Step terminal, rated voltage: 800 V, rated current: 24 A, connection type: Push-in connection, number of connections: 4, section: 0.14 mm² - 4 mm², AWG: 26 - 12, width: 5.2 mm, colour: black, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1094477 Terminal blocks (EC000897)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current I_n (EF008250)

24 A

Rated voltage (EF000228)
800 V

Type of electrical connection 1 (EF002526)
Other

Type of electrical connection 2 (EF002527)
Other

Number of clamp positions per level (EF002660)
4

Suitable for conductor material (EF012572)
Aluminium/copper

Mounting method (EF000003)
DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)
Other

Operating temperature (EF002393)
-60 °C

Inflammability class of insulation material according to UL94 (EF002521)
V0

Width (EF000008)
5.2 mm

Height (EF000040)
49 mm

Depth (EF000049)
43 mm

Explosion-tested version 'Ex e' (EF008498)
Yes

Closing plate required (EF002525)
Yes

Colour (EF000007)
Black

Internally connected stages (EF002661)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 2,5-QUATTRO BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.