

## INDUSTRIAL COMPONENT DATA

# PTS 4-PE 3213603 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 4-PE



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | PTS 4-PE              |
| Catalog number  | 3213603               |
| Category        | Ground terminal block |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-193DAECEFA         |
| Generated       | 2026-08-05            |

## Product Overview

Ground modular terminal block

Ground terminal, number of connections: 2, connection type: Push-in connection, 1st floor, cross-section: 0.2 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, color: yellow-green

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3213603

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 101 (C-1-2017)

GTIN 4055626084879

Weight per Piece (excluding packing) 13.720 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm<sup>2</sup>

Color green-yellow  
Insulating material PA  
Flammability rating according to UL 94 V0  
Area of application Machine building  
Plant engineering  
Process industry  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Open side panel Yes  
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Oscillation, broadband noise test result Test passed  
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03  
Test spectrum Service life test category 2, bogie-mounted  
Test frequency f1= 5 Hz to f2= 250 Hz  
ASD level 6.12 (m/s<sup>2</sup>)<sup>2</sup>/Hz  
Acceleration 3.12 g  
Test duration per axis 5 h  
Test directions X-, Y- and Z-axis  
Shock test result Test passed  
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03  
Shock form Half-sine  
Acceleration 30g  
Shock duration 18 ms  
Number of shocks per direction 3  
Test directions X-, Y- and Z-axis (pos. and neg.)  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material app...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 4-PE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.