


## INDUSTRIAL COMPONENT DATA

# PTSA 0,5/11-2,5-ZI GY 1715946 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 250 V, pitc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 0,5/11-2,5-ZI GY



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | PTSA 0,5/11-2,5-ZI GY          |
| Catalog number  | 1715946                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-1291D1395C                  |
| Generated       | 2026-08-05                     |

## Product Overview

Terminal for printed circuit board, rated voltage: 250 V, pitch: 2.5 mm, number of poles: 11, type of connection: spring clamp push-in, mounting: Soldering by wave, color: gray

Terminal block for printed circuit board, nominal current: 2 A, nominal voltage (III/2): 250 V, nominal cross-section: 0.5 mm<sup>2</sup>, number of potentials: 11, number of rows: 1, number of poles per row: 11, article family: PTSA 0.5, pitch: 2.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: gray, Pin arrangement: Zigzag Pins W, Pin length [P]: 3.6 mm, number of welding pins per potential: 1, packaging type: boxed

Printed circuit board terminal, nominal current: 2 A, rated voltage (III/2): 250 V, nominal cross section: 0.5 mm<sup>2</sup>, number of potentials: 11, number of rows: 1, number of positions per row: 11, product range: PTSA 0,5, pitch: 2.5 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: gray, Pin layout: Zigzag pinning W, Solder pin [P]: 3.6 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family PTSA 0,5

Product line COMBICON Terminals XS

Number of positions 11

Pitch 2.5 mm  
Number of connections 11  
Number of rows 1  
Number of potentials 11  
Pin layout Zigzag pinning W  
Solder pins per potential 1  
Data management status  
Article revision 00  
Electrical propertiesNominal current  $I_N$  2 A  
Nominal voltage  $U_N$  250 V  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 250 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 400 V  
Rated surge voltage (II/2) 2.5 kV  
Connection dataConnection technology  
Type PC termination block  
Nominal cross section 0.5 mm<sup>2</sup>  
Conductor connection  
Connection method Push-in spring connection  
Conductor cross section rigid 0.14 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>  
Conductor cross section AWG 24 ... 20  
Stripping length 9 mm  
MountingMounting type Wave soldering  
Pin layout Zigzag pinning W  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics hot-dip tin-plated  
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)  
Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)  
Material data - housing  
Color (Housing) gray (7042)  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability i...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 0,5/11-2,5-ZI GY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.