

INDUSTRIAL COMPONENT DATA

TTC-6-GDT-C-110AC-UT-I 2906844 PHOENIX CONTACT

Coarse surge protection with integrated status indicator for ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6-GDT-C-110AC-UT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6-GDT-C-110AC-UT-I
Catalog number	2906844
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-72A80E2A90
Generated	2026-08-06

Product Overview

Coarse surge protection with integrated status indicator for a signal wire with grounded reference potential.
Sufficient surge protection with integrated status indication for a signal conductor with grounded reference potential.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data
Orderkey 2906844
Packing unit 1 pc
Catalog page Page 151 (C-4-2019)
GTIN 4055626136998
Weight per Piece (excluding packing) 20.000 g
Custom tariff number 85363010
Country of origin DE (Germany)
Drawings
Ambient conditions
Protective circuit
Standards and Regulations
Classifications
Dimensions

General

Connection data

Environmental Product Compliance

Drawings

Diagram

Dimensional drawing

Circuit diagram

Back to topDimensions

Height 92 mm

Width 6.2 mm

Depth 69.5 mm (incl. DIN rail 7.5 mm)

Back to topAmbient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Altitude ≤ 2000 m (amsl (above mean sea level))

Degree of protection IP20 (with end cover)

Back to topGeneral

Housing material PBT

Flammability rating according to UL 94 V-0

Color traffic grey A RAL 7042

Mounting type DIN rail: 35 mm

Type DIN rail module, one-piece

Direction of action Line-Earth Ground

Back to topProtective circuit

IEC test classification C1

C2

C3

D1

Nominal voltage UN 110 V AC

Maximum continuous voltage UC 130 V AC

Rated current 2 A (60 °C)

Operating effective current I_{Cat} UC $\leq 1 \mu A$

Residual current IPE $\leq 1 \mu A$

Nominal discharge current $I_n(8/20) \mu s$ (line-earth) 5 kA

Pulse discharge current $I_{imp}(10/350) \mu s$ (line-earth) 0.5 kA

Voltage protection level U_p (line-earth) ≤ 800 V (C1 - 2 kV)

≤ 1 kV (C2 - 10 kV)

≤ 800 V (C3 - 25 A)

≤ 900 V (C3 - 100 A)

Response time t_A (line-earth) ≤ 100 n...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6-GDT-C-110AC-UT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.