

INDUSTRIAL COMPONENT DATA

PTSA 1,5/ 6-3,5-Z MCGY/BK 1001321 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 400 V, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 1,5/ 6-3,5-Z MCGY/BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSA 1,5/ 6-3,5-Z MCGY/BK
Catalog number	1001321
Category	Printed circuit board terminal
Minimum order	160 Pcs
Document ID	EO-EB51CD8657
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 3.5 mm, number of poles: 6, type of connection: spring clamp push-in, mounting: Soldering by wave, color: multicolor

Printed circuit board terminal, rated current: 8 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 6, Number of rows: 1, Number of poles per row: 6, item family: PTSA 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave welding, connection direction conductor/printed circuit board: 45°, color: multicolor, Pin layout: Zigzag pins M, Pin length [P]: 3.6 mm, Packing type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Terminal for printed circuits, nominal current: 8 A, rated voltage: 400 V, pitch: 3.5 mm, number of poles: 6, connection: spring-clamp Connection Push-in, mounting: Soldering wave, the direction of connection wire/board: 45 °, color: more colors
Commercial data

The code for the order One million one thousand three hundred twenty one

Pieces/pack. 160 PCS

Sales key AACBAA -

The amount of minimum order 160 PCS

GTIN Four trillion fifty five billion six hundred twenty six million four hundred sixty nine thousand eight hundred forty three

Weight per piece (package included) 2,896 g

Number customs tariff Eighty five million three hundred sixty nine thousand ten

Size

Length [l] 12 mm
Step 3.5 mm
Measure 17.5 mm
Width [w] 22.5 mm
Mounting height 13.1 mm
Height [h] 16.7 mm
Length of pin [P] 3.6 mm
Distance shanks 3.5 mm
Hole diameter 1 mm

General

Family article PTSA 1,5
Nominal section 1.5 mm²
Surface of the pin welding
N. of poles Six
Environmental Product Compliance
China RoHS Period for proper use: unlimited = EFUP-and
Any hazardous substances above the threshold values

Rankings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty one thousand one hundred
eCl@ss 6.0 Twenty seven million two hundred sixty one thousand one hundred
eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred one
eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred one
eCl@ss 9.0 Twenty seven million four hundred forty thousand four hundred one

ETIM

ETIM 5.0 EC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 1,5/ 6-3,5-Z MCGY/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.