

INDUSTRIAL COMPONENT DATA

PTSA 1,5/ 8-3,5-F BK 1825094 PHOENIX CONTACT Printed circuit board terminal, rated current: 8 A, rated volta..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSA 1,5/ 8-3,5-F BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSA 1,5/ 8-3,5-F BK
Catalog number	1825094
Category	Printed circuit board terminal
Minimum order	120 Pcs
Document ID	EO-5E9E349CC1
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 8 A, rated voltage (III/2): 250 V, rated cross-section: 1.5 mm², number of rows: 1, number of poles per row: 8, item family: PTSA 1.5, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 45 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of welding pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSA 1,5/ 8-3,5-F BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.