

INDUSTRIAL COMPONENT DATA

PTSM 0,5/ 4-PI-2,5 WH 1709452 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSM 0,5/ 4-PI-2,5 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTSM 0,5/ 4-PI-2,5 WH
Catalog number	1709452
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-04FC143757
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 0.5 mm², color: white, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PTSM 0.5/.. -PI WH, pitch: 2.5 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON PTSM, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1709452

Packing unit 250 pc

Minimum order quantity 250 pc

GTIN 4055626130378

Weight per Piece (excluding packing) 1.060 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 15.5 mm

Width [w] 11.7 mm

Height [h] 5 mm

Pitch 2.5 mm

Dimension a 7.5 mm

General

Range of articles PTSM 0,5/...-PI WH

Number of positions 4

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 1.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 100 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 6 A

Nominal cross section 0.5 mm²

Maximum load current 6 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 6 mm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 0.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.34 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 20

Standards and Regulations

Connection in acc. with standard....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSM 0,5/ 4-PI-2,5 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.