

INDUSTRIAL COMPONENT DATA

BP 4-4CT 3208723 PHOENIX CONTACT Short-circuit connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BP 4-4CT



Manufacturer	PHOENIX CONTACT
MPN / Reference	BP 4-4CT
Catalog number	3208723
Category	Test plug for terminal blocks
Minimum order	10 Pcs
Document ID	EO-CC66D95994
Generated	2026-08-06

Product Overview

Short-circuit connector

Connector for four current transformers, each with a forward transformer short circuit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3208723

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626437552

Weight per Piece (excluding packing) 109.980 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 8

Number of levels 1

Number of connections 8

Potentials 8

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Ambient temperature (operation) -50 °C ... 100 °C

Ambient temperature (assembly) -40 °C ... 100 °C

Maximum load current 30 A

Nominal current I_N 15 A

Nominal voltage U_N 320 V

Open side panel No

Dimensions

Width 74.4 mm

Length 40 mm

Height 57.3 mm

Pitch 6.1 mm

Connection data

Connection method Bolt connection

Screw thread M4

Stripping length 8 mm ... 9 mm

Tightening torque, min 1.2 Nm

Tightening torque max 1.5 Nm

Connection in acc. with standard IEC 61984

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 14

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 2.5 mm²

Min. AWG conductor cross section, flexible 20

Max. AWG conductor cross section, flexible 14

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²

Conductor cross section fle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BP 4-4CT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.