

**INDUSTRIAL COMPONENT DATA**

# PTTB 4-HESILED 250 (5X20) 3211892 PHOENIX CONTACT

## Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTB 4-HESILED 250 (5X20)



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | PHOENIX CONTACT           |
| MPN / Reference | PTTB 4-HESILED 250 (5X20) |
| Catalog number  | 3211892                   |
| Category        | Fuse terminal block       |
| Minimum order   | 50 Pcs                    |
| Document ID     | EO-52DA765F13             |
| Generated       | 2026-08-06                |

### Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 500 V, nominal current: 28 A, connection type: Push-in connection, 1st floor, Sizing section: 4 mm<sup>2</sup>, cross-section: 0.2 mm<sup>2</sup>- 6 mm<sup>2</sup>, connection type: Push-in connection, 2. Floor, Sizing cross-section: 4 mm<sup>2</sup>, cross-section: 0.2 mm<sup>2</sup>- 6 mm<sup>2</sup>, Mounting class: NS 35/7.5, NS 35/15, color: black

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

### Additional Product Information

Key Commercial Data

Orderkey 3211892

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 95 (C-1-2017)

GTIN 4055626380575

Weight per Piece (excluding packing) 24.000 g

Custom tariff number 85369095

Country of origin CN (China)

General

Note The current is determined by the fuse used, the voltage by the light indicator.

Number of levels 2  
Number of connections 4  
Nominal cross section 4 mm<sup>2</sup>  
Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 1.02 W  
Fuse G / 5 x 20  
Fuse type Glass / ceramics / ...  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)  
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)  
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)  
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)  
LED voltage range 110 V AC/DC ... 250 V AC/DC  
LED current range 0.41 mA ... 0.96 mA  
Connection in acc. with standard IEC 60947-7-1  
Maximum load current 32 A  
Nominal current I<sub>N</sub> 28 A  
Nominal voltage U<sub>N</sub> 500 V  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current (upper level) 6.3 A (the current is determined by the fuse used)  
Nominal current I<sub>N</sub>(upper level) 6.3 A  
Nominal voltage....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTB 4-HESILED 250 (5X20) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.