

INDUSTRIAL COMPONENT DATA

PTTBS 2,5-DIO/O-U CUS 1026165 PHOENIX CONTACT

Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBS 2,5-DIO/O-U CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTBS 2,5-DIO/O-U CUS
Catalog number	1026165
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-00E012BA8F
Generated	2026-08-02

Product Overview

Component terminal block

Component terminal block, with integrated diode 1N4007, detectable switching symbol in mounted state, nominal voltage: 500 V, nominal current: 0.5 A, number of connections: 4, connection type: Push-in connection, 1st and 2nd floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 1026165

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626518787

Weight per Piece (excluding packing) 12.660 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note The max. current is determined by the diode. Installed: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous current: 0.5 A.

Number of levels 2
Number of connections 4
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Nominal current I_N 20 A
Maximum load current 26 A (with 4 mm² conductor cross section)
Nominal voltage U_N 500 V
Open side panel Yes
Dimensions
Width 5.2 mm
Length 78 mm
Height NS 35/7,5 55 mm
Height NS 35/15 62.5 mm
Connection data
Connection method Push-in connection
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBS 2,5-DIO/O-U CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.