

INDUSTRIAL COMPONENT DATA

PTTBS 2,5/U-OG/O-GN 3209609 PHOENIX CONTACT

Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBS 2,5/U-OG/O-GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTBS 2,5/U-OG/O-GN
Catalog number	3209609
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-7A8392815D
Generated	2026-08-05

Product Overview

Double-level terminal block

Double-deck terminal block, with pusher down orange and top green, cross-section: 0.14 mm² - 4 mm², AWG: 26 - 12, connection type: push-in connection, width: 5.2 mm, color: gray, mounting type: NS 35/7.5, NS 35/15

Double-level terminal block, with orange lower pusher and upper green pusher, cross section: 0.14 mm² - 4 mm², AWG: 26 - 12, connection method: push-in connection, width: 5.2 mm, color: gray, mounting type: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Multi-level terminal block

Number of connections 4

Number of rows 2

Potentials 2

Data management status

Article revision 09

Insulation characteristics

Overvoltage category III

Electrical propertiesRated surge voltage 6 kV

Maximum power dissipation for nominal condition 0.77 W

Connection dataNumber of connections per level 2

Nominal cross section 2.5 mm²
1st and 2nd level
Stripping length 10 mm
Internal cylindrical gage A3
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 4 mm²
Cross section AWG 26 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²
Nominal current 22 A
Maximum load current 24 A (with 4 mm² conductor cross section, rigid)
Nominal voltage 500 V
Nominal cross section 2.5 mm²
1st and 2nd level Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 4 mm²
Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm² ... 2.5 mm²
Ex data Rated data (ATEX/IECEx)
Identification ? II 2 GD Ex....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBS 2,5/U-OG/O-GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.