


INDUSTRIAL COMPONENT DATA

PTTBS 2,5 YE 1037089 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBS 2,5 YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTBS 2,5 YE
Catalog number	1037089
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-F8D6B03E7D
Generated	2026-08-03

Product Overview

Double-level terminal block

Double-level terminal block, nominal voltage: 500 V, nominal current: 22 A, connection type: Push-in connection, 1st and 2nd floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 1037089

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626570600

Weight per Piece (excluding packing) 12.400 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 2

Number of connections 4

Nominal cross section 2.5 mm²
Color yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 22 A
Maximum load current 24 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel Yes
Dimensions
Width 5.2 mm
Length 78 mm
Height NS 35/7,5 55 mm
Height NS 35/15 62.5 mm
Connection data
Connection method Push-in connection
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
2 conducto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBS 2,5 YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.