

INDUSTRIAL COMPONENT DATA

PTTBV 4-PV 1088939 PHOENIX CONTACT Double-deck terminal block, nominal voltage: 1000 V, Thermal constant cur..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBV 4-PV



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTBV 4-PV
Catalog number	1088939
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-D1B9D73BFD
Generated	2026-08-01

Product Overview

Double-deck terminal block, nominal voltage: 1000 V, Thermal constant current I_{Th}: 28 A, connection type: Push-in connection, 1st and 2nd floor, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

Double-decker terminal, connection type: Push-in connection, section: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, color: grey, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1088939 Terminal blocks (EC000897)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.2 mm²

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Rated voltage (EF000228)
1000 V

Type of electrical connection 1 (EF002526)
Other

Type of electrical connection 2 (EF002527)
Other

Number of levels (EF002659)
2

Number of clamp positions per level (EF002660)
2

Suitable for conductor material (EF012572)
Aluminium/copper

Mounting method (EF000003)
DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)
Other

Inflammability class of insulation material according to UL94 (EF002521)
V0

Width (EF000008)
6.2 mm

Height (EF000040)
99.5 mm

Depth (EF000049)
56 mm

Closing plate required (EF002525)
Yes

Colour (EF000007)
Grey

Internally connected stages (EF002661)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBV 4-PV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.