


INDUSTRIAL COMPONENT DATA

PT 1,5/ 8-PH-3,5 BD:9-16 1702360 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 8-PH-3,5 BD:9-16



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 8-PH-3,5 BD:9-16
Catalog number	1702360
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-1A2588E3DD
Generated	2026-08-05

Product Overview

PCB connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, dimensioning voltage (III/2): 200 V, contact surface: Tin, contact type: Female connection, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, number of connections: 8, family of articles: PT 1.5/.. -PH, pitch: 3.5 mm, connection type: Screw connection with wire protection bracket, conductor connection direction/printed circuit board: 0 °, Stecksystem: COMBICON COMPACT PST 1, Lock: without, packaging type: boxed

Printed circuit board connector, nominal section: 1.5 mm², nominal current: 8 A, nominal voltage (III/2): 200 V, contact surface: Sn, contact connection type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: PT 1.5/.. -PH, pitch: 3.5mm, connection type: Screw connection with wire protection bracket, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON PST 1.0, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1702360

Packing unit 1

GTIN 4046356583848

Custom tariff number 85366990

Dimensions

Length [l] 11 mm

Width [w] 28 mm

Height [h] 11 mm

Pitch 3.5 mm

Dimension a 24.5 mm

General

Range of articles PT 1,5/..-PH

Number of positions 8

Connection method Screw connection with wire protector

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²**Connection data**Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.2 mm²2 conductors with same cross section, solid max. 0.34 mm²2 conductors with same cross section, stranded min. 0.2 mm²2 conductors with same cross section, stranded max. 0.5 mm²**Standards and Regulations**

Connection in acc. with standard EN-VDE

CUL**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

ClassificationseCl@ss 4.0272607XXeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.02...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 8-PH-3,5 BD:9-16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.