


INDUSTRIAL COMPONENT DATA

PTU 4 WH 3211865 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTU 4 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTU 4 WH
Catalog number	3211865
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-3C160DA05E
Generated	2026-08-02

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 32 A, connection type: Push-in connection, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, colour: white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3211865

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626349749

Weight per Piece (excluding packing) 10.770 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color white

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Connection method Push-in connection

Connection in acc. with standard IEC 60947-7-1

Maximum load current 38 A (the maximum load current must not be exceeded by the total current of all connected conductors)

Nominal current I_N 32 A

Nominal voltage U_N 800 V

Connection method Screw connection

Connection in acc. with standard IEC 60947-7-1

Maximum load current 38 A (with 6 mm² conductor connection)

Nominal current I_N 32 A

Nominal voltage U_N 800 V

Open side panel Yes

Dimensions

Width 6.2 mm

Length 58.8 mm

Height NS 35/7,5 42.8 mm

Height NS 35/15 50.3 mm

End cover width 2.2 mm

Connection data

Connection method Push-in connection

Connection in acc. with standard IEC 60947-7-1

Stripping length 10 mm ... 12 mm

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTU 4 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.