

INDUSTRIAL COMPONENT DATA

PTV 2,5-QUATTRO-MT 1079070 PHOENIX CONTACT Blade interruptible terminal block, nominal voltage: 400 V, nomin..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTV 2,5-QUATTRO-MT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTV 2,5-QUATTRO-MT
Catalog number	1079070
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-C419B6C271
Generated	2026-08-04

Product Overview

Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 20 A, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², colour: grey

Interruptible terminal per blade, rated voltage: 400 V, rated current: 20 A, connection type: Push-in connection, section: 0.14 mm² - 4 mm², AWG: 26 - 12, length: 80.5 mm, width: 5.2 mm, color: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1079070 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current I_n (EF008250)

20 A

Rated voltage (EF000228)

400 V
Type of electrical connection 1 (EF002526)
Other
Type of electrical connection 2 (EF002527)
Other
Number of clamp positions per level (EF002660)
4
Internally connected stages (EF002661)
Yes
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
5.2 mm
Height (EF000040)
80.5 mm
Depth (EF000049)
45.7 mm
Closing plate required (EF002525)
Yes
Colour (EF000007)
Grey
Type of cross disconnection (EF002546)
None
With integrated test socket (EF002547)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV 2,5-QUATTRO-MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.