

**INDUSTRIAL COMPONENT DATA**

# PTV 2,5-QUATTRO-MT BU 1079071 PHOENIX CONTACT Blade interruptible terminal block, nominal voltage: 400 V, no..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTV 2,5-QUATTRO-MT BU



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | PTV 2,5-QUATTRO-MT BU             |
| Catalog number  | 1079071                           |
| Category        | (Knife) disconnect terminal block |
| Minimum order   | 50 Pcs                            |
| Document ID     | EO-242908D905                     |
| Generated       | 2026-08-06                        |

## Product Overview

Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 20 A, connection type: Push-in connection, Sizing cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, color: blue

Interruptible terminal per blade, rated voltage: 400 V, rated current: 20 A, connection type: Push-in connection, section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, length: 80.5 mm, width: 5.2 mm, colour: blue

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

ETIM for 1079071 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm<sup>2</sup>

Connectable conductor cross section solid-core (EF007337)

0.14 mm<sup>2</sup>

Rated current I<sub>n</sub> (EF008250)

20 A

Rated voltage (EF000228)

400 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

4

Internally connected stages (EF002661)

Yes

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

5.2 mm

Height (EF000040)

80.5 mm

Depth (EF000049)

45.7 mm

Closing plate required (EF002525)

Yes

Colour (EF000007)

Blue

Type of cross disconnection (EF002546)

None

With integrated test socket (EF002547)

No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV 2,5-QUATTRO-MT BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.