

INDUSTRIAL COMPONENT DATA

PTV 2,5-QUATTRO-TG 1079072 PHOENIX CONTACT The maximum load current must not be exceeded by the sum current ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTV 2,5-QUATTRO-TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTV 2,5-QUATTRO-TG
Catalog number	1079072
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-6329C43182
Generated	2026-08-04

Product Overview

The maximum load current must not be exceeded by the sum current of all connected conductors. The current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 20 A, connection type: Push-in connection, Dimensioning section: 2.5 mm², section: 0.14 mm² - 4 mm², color: gray
 Interruptible terminal, rated voltage: 400 V, rated current: 20 A, connection type: Push-in connection, section: 0.14 mm² - 4 mm², AWG: 26 - 12, length: 80.5 mm, width: 5.2 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

ETIM for 1079072 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current In (EF008250)

20 A

Rated voltage (EF000228)

400 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

4

Internally connected stages (EF002661)

Yes

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

5.2 mm

Height (EF000040)

80.5 mm

Depth (EF000049)

45.7 mm

Closing plate required (EF002525)

Yes

Colour (EF000007)

Grey

Type of cross disconnection (EF002546)

None

With integrated test socket (EF002547)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV 2,5-QUATTRO-TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.