

INDUSTRIAL COMPONENT DATA

PTV 4-MT BU 1088740 PHOENIX CONTACT Blade interruptible terminal block, nominal voltage: 500 V, nominal curr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTV 4-MT BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTV 4-MT BU
Catalog number	1088740
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-548E1429C4
Generated	2026-08-03

Product Overview

Blade interruptible terminal block, nominal voltage: 500 V, nominal current: 20 A, 1st floor, connection type: Push-in connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: blue Interruptible terminal per blade, rated voltage: 500 V, rated current: 20 A, connection type: Push-in connection, section: 0.2 mm² - 6 mm², AWG: 24 - 10, length: 63.3 mm, width: 6.2 mm, colour: blue, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1088740 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.2 mm²

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Rated current I_n (EF008250)

20 A

Rated voltage (EF000228)

500 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

2

Internally connected stages (EF002661)

Yes

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

6.2 mm

Height (EF000040)

63.3 mm

Depth (EF000049)

36.8 mm

Closing plate required (EF002525)

Yes

Colour (EF000007)

Blue

Type of cross disconnection (EF002546)

None

With integrated test socket (EF002547)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV 4-MT BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.