

INDUSTRIAL COMPONENT DATA

PTV 4-QUATTRO 1088734 PHOENIX CONTACT Feed-through terminal, nominal voltage: 1000 V, nominal current: 32 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTV 4-QUATTRO



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTV 4-QUATTRO
Catalog number	1088734
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-1D90D94F2F
Generated	2026-08-03

Product Overview

Feed-through terminal, nominal voltage: 1000 V, nominal current: 32 A, number of connections: 4, connection type: Push-in connection, 1st floor, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

Step terminal, rated voltage: 1000 V, rated current: 32 A, connection type: Push-in connection, number of connections: 4, section: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, height: 45.7 mm, colour: grey, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

ETIM for 1088734 Terminal blocks (EC000897)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.2 mm²

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Rated current I_n (EF008250)

32 A
Rated voltage (EF000228)
1000 V
Type of electrical connection 1 (EF002526)
Other
Type of electrical connection 2 (EF002527)
Other
Number of clamp positions per level (EF002660)
4
Suitable for conductor material (EF012572)
Aluminium/copper
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Operating temperature (EF002393)
-60 °C
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
6.2 mm
Height (EF000040)
69.2 mm
Depth (EF000049)
45.7 mm
Explosion-tested version 'Ex e' (EF008498)
Yes
Closing plate required (EF002525)
Yes
Colour (EF000007)
Grey
Internally connected stages (EF002661)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV 4-QUATTRO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.