

INDUSTRIAL COMPONENT DATA

PTVC 2,5-TG 1079061 PHOENIX CONTACT Interruptible terminal, Current and voltage are determined by the connec..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTVC 2,5-TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTVC 2,5-TG
Catalog number	1079061
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-5A10470138
Generated	2026-08-05

Product Overview

Interruptible terminal, Current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 20 A, connection type: Push-in connection, Dimensioning section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, color: gray

Interruptible terminal, rated voltage: 800 V, rated current: 24 A, connection type: Push-in connection, section: 0.14 mm² - 4 mm², AWG: 26 - 12, length: 50.8 mm, width: 5.2 mm, colour: grey, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1079061 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Rated current I_n (EF008250)

20 A

Rated voltage (EF000228)
400 V

Type of electrical connection 1 (EF002526)
Other

Type of electrical connection 2 (EF002527)
Other

Number of clamp positions per level (EF002660)
2

Internally connected stages (EF002661)
Yes

Mounting method (EF000003)
DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)
Other

Inflammability class of insulation material according to UL94 (EF002521)
V0

Width (EF000008)
5.2 mm

Height (EF000040)
50.8 mm

Depth (EF000049)
35.3 mm

Closing plate required (EF002525)
Yes

Colour (EF000007)
Grey

Type of cross disconnection (EF002546)
None

With integrated test socket (EF002547)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTV C 2,5-TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.