

**INDUSTRIAL COMPONENT DATA**

# PTVFIX 12X2,5-NS35A GY 1019532 PHOENIX CONTACT

## Distribution block, nominal voltage: 690 V, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTVFIX 12X2,5-NS35A GY



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTVFIX 12X2,5-NS35A GY      |
| Catalog number  | 1019532                     |
| Category        | Feed-through terminal block |
| Minimum order   | 10 Pcs                      |
| Document ID     | EO-EBC8F50BBD               |
| Generated       | 2026-08-04                  |

### Product Overview

Distribution block, nominal voltage: 690 V, nominal current: 24 A, number of connections: 12, number of poles: 1, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, colour: grey

Distribution block, rated voltage: 690 V, rated current: 24 A, connection type: Push-in connection, Sizing section: 2.5 mm<sup>2</sup>, section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, color: grey

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; FIX block System

### Additional Product Information

ETIM for 1019532 Terminal blocks (EC000897)

Feature Name

Feature Value

Rated current In (EF008250)

24 A

Rated voltage (EF000228)

690 V

Type of electrical connection 1 (EF002526)

Other

Type of electrical connection 2 (EF002527)

Other

Number of clamp positions per level (EF002660)

12

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Material insulation body (EF007543)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Width (EF000008)

31.1 mm

Height (EF000040)

45.7 mm

Depth (EF000049)

29.2 mm

Closing plate required (EF002525)

No

Colour (EF000007)

Grey

Internally connected stages (EF002661)

Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTVFIX 12X2,5-NS35A GY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.