


INDUSTRIAL COMPONENT DATA

VS-ASI-FC-PUR-YE 100M 1404883 PHOENIX CONTACT

Flat-ribbon conductor

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-ASI-FC-PUR-YE 100M



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-ASI-FC-PUR-YE 100M
Catalog number	1404883
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-53DAB6D381
Generated	2026-08-06

Product Overview

Flat-ribbon conductor

AS-Interface PUR flat cable in yellow, 2 x 1.5 mm², 100 m reelAS-Interface PUR flat conductor in yellow, 2 x 1.5 mm², 100 m ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable by the meter

Sensor type AS-Interface

Number of positions 2

Electrical propertiesRated voltage (III/3) 32 V

Rated surge voltage 2 kV

InterfacesSignal type/category AS-Interface

DimensionsWidth 10 mm

Height 4 mm

Cable/lineCable length 100 m

Cable weight 64 kg/km

Number of positions 2

Shielded no

Conductor structure 2 x 1.5 mm²

Conductor type Flat cable
Conductor structure signal line 84x 0.15 mm
AWG signal line 16
Conductor cross section 1.5 mm²
Wire diameter incl. insulation 2.5 mm
Outer sheath, material PUR
External sheath, color lemon yellow RAL 1012
Conductor material Tin-plated Cu litz wires
Material wire insulation PP
Single wire, color brown, blue
Thickness, insulation approx. 0.50 mm
Max. conductor resistance $\leq 13.7 \text{ } \Omega/\text{km}$
Insulation resistance $\geq 1 \text{ M}\Omega\cdot\text{km}$
Nominal voltage, cable 32 V
Test voltage 2000 V
Smallest bending radius, fixed installation $\geq 6 \text{ mm}$ (one-time)
Dynamic load capacity (bending) Max. bending cycles: 8000000, Bending radius: 75 mm, Traversing direction: horizontal, above the broadside, Traversing rate: 4 m/s, Acceleration: 4 m/s²
Max. bending cycles: 10000000, Bending radius: 50 mm, Traversing direction: vertical, above the broadside
Halogen-free yes
Special properties Silicone-free
Ambient temperature (operation) -40 °C ... 85 °C (cable, fixed installation)
-30 °C ... 85 °C (Cable, flexible installation)
Environmental and real-life conditions Ambient conditions
Ambient temperature (operation) -30 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-ASI-FC-PUR-YE 100M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.