

INDUSTRIAL COMPONENT DATA

PV-FT-C2F-C-2,5-75-BU-FLC 1463064 PHOENIX CONTACT

Photovoltaic connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PV-FT-C2F-C-2,5-75-BU-FLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PV-FT-C2F-C-2,5-75-BU-FLC
Catalog number	1463064
Category	Sensor-actuator connector chassis
Minimum order	200 Pcs
Document ID	EO-7665F0358D
Generated	2026-08-04

Product Overview

Photovoltaic connector
Photovoltaic plug-in connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data
Orderkey 1463064
Packing unit 200 pc
Note Made to Order (non-returnable)
GTIN 4046356757393
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 85359000
Country of origin DE (Germany)
Dimensions
Fixed cable length 75 mm
Ambient conditions
Degree of protection (when plugged in) IP66 / IP68 (2 m / 24 h)
Degree of protection (not plugged in) IP65
Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -25 °C ... 50 °C

General

Design Socket

Tightening torque nut 1.8 Nm $\pm$ 0.1 Nm

Insertion force 45 N $\pm$ 10 N

Disconnect force 250 N $\pm$ 50 N

Pull-out force of cable $\geq$ disconnect force > 80 N

Rated voltage 1500 V

Rated current (2.5 mm²) 27 A

Rated current (4.0 mm²)

Rated current (6.0 mm²)

Nominal cross section 2.5 mm²

Protection class II

Material

Color black

Insulating material mPPE

Contact material Cu

Contact surface material Ag

Flammability rating according to UL 94 V0

Connection data

Connection method Crimp

Connection capacity 2.5 mm²

Contact resistance with connected conductor 0.45 m Ω

Cable type S01

Conductor

Outer sheath, material PE-X

External sheath, color blue

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440102eCl@ss 8.027440102eCl@ss 9.0274...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PV-FT-C2F-C-2,5-75-BU-FLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.