

INDUSTRIAL COMPONENT DATA

PV-FT-C3M-C-2,5-4-VPE50 1196770 PHOENIX CONTACT

Crimp contact, Article family: SUNCLIX, number of poles: 1, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PV-FT-C3M-C-2,5-4-VPE50



Manufacturer	PHOENIX CONTACT
MPN / Reference	PV-FT-C3M-C-2,5-4-VPE50
Catalog number	1196770
Category	Contact for industrial connectors
Minimum order	50 Pcs
Document ID	EO-F8640500E1
Generated	2026-08-06

Product Overview

Crimp contact, Article family: SUNCLIX, number of poles: 1, min. conductor cross-section: 2.5 mm², max. conductor cross-section: 4 mm², rated current: 27 A, Connection type: Crimping, Contact connection type: Male

Crimp Contact, Item Family: Sunclix, Pole Number: 1, Min. Conductor Cross-Section: 2.5 mm², Max. Conductor Cross-Section: 4 mm², Rated Current: 27 A, Connection Type: Crimp, Contact Connection Type: Male

Crimp contact, Product series: Sunclix, number of poles: 1, Min. conductor cross-section: 2.5 mm², Max. conductor cross-section: 4 mm², Rated current: 27 A, Connection type: Crimping, Contact connection type: Plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Technical dataNotesSafety Warning

Safety instructions • **WARNING:** Only operate products in perfect condition. Regularly check the products for damage. Immediately take out defective products. Replace the damaged products. The item cannot be repaired.

• **WARNING:** Have the product installed and operated only by qualified electrical personnel in accordance with the following safety instructions. Specialists must be familiar with the basics of electrical engineering and must be able to recognize and avoid hazards. The corresponding symbol on the packaging indicates that the intervention of qualified electrical personnel is required.

WARNING: Connectors must not be connected or disconnected under load. Failure to comply with it and use it in accordance with the rules may result in damage to persons and/or property.

• The products are suitable for the areas of system assembly, control and assembly of electrical appliances.

- Packaged products must not be handled or opened incorrectly.
- Only use plugs specified in the standards specified in the technical data (e.g. those listed in the product accessories on the phoenixcontact.com/products website).
- If you use the product directly in conjunction with third-party products, you are entirely responsible for this.
- For operating voltages > 50 VAC, conductive connector housings must be grounded
- Make sure that the protective or operating ground is properly engaged.
- Observe the respective technical data. The information is given in t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PV-FT-C3M-C-2,5-4-VPE50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.