

INDUSTRIAL COMPONENT DATA

Q 0,75/3A50/9-9KU-ESA BK 1642072 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 0,75/3A50/9-9KU-ESA BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q 0,75/3A50/9-9KU-ESA BK
Catalog number	1642072
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-1615DF9F9C
Generated	2026-08-06

Product Overview

Panel feed-through

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1642072

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4017918895570

Weight per Piece (excluding packing) 33.180 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.

Length of cable 0.5 m

Color black

Connection method QUICKON connection

Single litz wires 50 cm long; 0.75 mm²

Note on the internal connection method Pos. 1: Brown; pos. 2: White; pos. 3: Blue

Number of positions 3

Wrench size, union nut 19 mm

Tightening torque, union nut 2.5 Nm

Wrench size, contact carrier 19 mm

Tightening torque contact carrier 3.75 Nm

Tightening torque, counter nut 3.75 Nm

Conductor cross section flexible min. 0.34 mm²

Conductor cross section flexible max. 0.75 mm²

Cabel

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter Class 2-6 // 0.34 mm²: 0.1 mm; 0.5 - 0.75 mm²: 0.15 mm

Wire insulation material PVC / PE

Wire diameter including insulation 2.5 mm

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -25 °C ... 80 °C (Specifications of the cable manufacturer must be observed.)

-25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.)

Electrical characteristics

Nominal current I_N 9 A

Rated voltage (III/3) 160 V

Note on the rated voltage (III/3) wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 0,75/3A50/9-9KU-ESA BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.