

INDUSTRIAL COMPONENT DATA

Q 1,5/3FS/13-13KU-ESA BK 1670989 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 1,5/3FS/13-13KU-ESA BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q 1,5/3FS/13-13KU-ESA BK
Catalog number	1670989
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-330E84CA2B
Generated	2026-08-06

Product Overview

Panel feed-through

Feedthrough, QUICKON connection, 250 V, 17.5 A, black

Panel feed-through, connection method: Manual solder/slip on connection/ IDC connection, M20, 0.75 mm² ... 1.5 mm², 500 V, 17.5 A, black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Panel feed-through

Number of positions 3

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Connection dataConnection technology

Connection method On the device side Manual solder/slip on connection

Connection method On the field side IDC connection

Frequency of connections between conductors of the same cross section 10 (if the conductor is connected more than once, seal and cap may need to be replaced.)

Conductor connection

Conductor cross section flexibel 0.75 mm² ... 1.5 mm²

Conductor cross section solid 0.75 mm² ... 1 mm²

Connection cross section AWG 18 ... 16

Tightening torque Union nut 2.5 Nm

Tightening torque Contact carrier 3.75 Nm

Tightening torque Locking nut 3.75 Nm

Wrench size Union nut 24 mm

Wrench size Contact carrier 24 mm

Electrical properties Rated surge voltage (II/2) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (III/3) 6 kV

rated voltage (II/2) 630 V (with insulating sleeve)

rated voltage (III/2) 320 V (with insulating sleeve)

Rated voltage (III/3) 500 V

Nominal voltage UN 500 V AC

500 V DC

Nominal current I_N 17.5 A

Material specifications Color black (RAL 9005)

Flammability rating according to UL 94 V0

Material wire insulation PVC / PE

Contact material Copper alloy

Contact surface material Pre-nickel plated and tin-plated

Contact carrier material PA 6.6

Cable/line Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 Cl.2-5, min. wire diameter 0.2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 1,5/3FS/13-13KU-ESA BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.