

## INDUSTRIAL COMPONENT DATA

# Q 1,5/4FL/24-M20KU-ESA L/N BK 1418315 PHOENIX CONTACT Panel feed-through Q 1,5/4FL/24-M20KU-ESA L/N BK 14183..

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 1,5/4FL/24-M20KU-ESA L/N BK



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | Q 1,5/4FL/24-M20KU-ESA L/N BK     |
| Catalog number  | 1418315                           |
| Category        | Sensor-actuator connector chassis |
| Minimum order   | 250 Pcs                           |
| Document ID     | EO-0C7C82F900                     |
| Generated       | 2026-08-06                        |

## Product Overview

Panel feed-through - Q 1,5/4FL/24-M20KU-ESA L/N BK - 1418315

Panel feed-through, for external wall mounting, with manual solder/slip-on connection, 4.8 x 0.8 mm, connecting thread M20x1.5, 4-pos.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                     |
|--------------|-----------------------------------------------------|
| Catalog path | PHOENIX CONTACT > QUICKON Installation System (QPD) |
|--------------|-----------------------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Panel feed-through

Number of positions 4

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Connection dataConnection technology

Frequency of connections between conductors of the same cross section 10

Electrical propertiesNominal voltage UN 500 V

Nominal current IN 15 A (15 A with slip-on sleeve 2.5 mm<sup>2</sup>; 12 A with slip-on sleeve 1.5 mm<sup>2</sup>.)

Material specificationsColor black (RAL 9005)

Flammability rating according to UL 94 V0

Environmental and real-life conditions Ambient conditions

Degree of protection IP65

IP67

Impact strength IK07

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 1,5/4FL/24-M20KU-ESA L/N BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.