

INDUSTRIAL COMPONENT DATA

QPD W 4X2,5 M25 0,25 GY AE B-S 1419428 PHOENIX CONTACT Panel feed-through QPD W 4X2,5 M25 0,25 GY AE B-S 141..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD W 4X2,5 M25 0,25 GY AE B-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD W 4X2,5 M25 0,25 GY AE B-S
Catalog number	1419428
Category	Sensor-actuator connector chassis
Minimum order	250 Pcs
Document ID	EO-EB18F778C2
Generated	2026-08-05

Product Overview

Panel feed-through - QPD W 4X2,5 M25 0,25 GY AE B-S - 1419428

Feedthrough, QUICKON connection, number of poles: 4, 1 mm² ... 2.5 mm², 690 V, 20 A, grey, without QUICKON nut, Single conductors (welded), 2.5 mm², at end with ferrules, cable length: 0.25 m, Pin arrangement: 1 = BN, 2 = BU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Panel feed-through, QUICKON connection, number of positions: 4, 1 mm² ... 2.5 mm², 690 V, 20 A, gray, Without QUICKON nut, Single wires (welded-on), 2.5 mm², with ferrules at the end, cable length: 0.25 m, pin assignment: 1 = BN, 2 = BU

Key Commercial Data

Orderkey 1419428

Packing unit 1

GTIN 4055626173054

Custom tariff number 85444290

General

Type QPD 4x2,5

Length of cable 0.25 m

Color gray
Locking type Screw locking
Connection method QUICKON connection
IDC connection
Number of positions 4
Tightening torque, union nut 5 Nm
Tightening torque, counter nut 5 Nm
Number of connections 10
Conductor cross section flexible min. 1 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section solid min. 1 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 14
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm
Wire insulation material PVC / PE
Wire diameter including insulation 2 mm ... 3.8 mm
Conductor cross section 2.5 mm²
Position marking 1, 2, 3, 4
Ambient conditions
Degree of protection IP66
IP68 (2 m / 24 h)
Ambient temperature (operation) -40 °C ... 100 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Temperature when conductor connected -5 °C ... 50 °C
Electrical characteristics
Nominal current I_N 20 A
Rated current 20 A
Rated voltage (III/3) 690 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Rated surge voltage (I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD W 4X2,5 M25 0,25 GY AE B-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.