


INDUSTRIAL COMPONENT DATA

QTTCB 1,5 RD 3205118 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: QTTCB 1,5 RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	QTTCB 1,5 RD
Catalog number	3205118
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-629CF59703
Generated	2026-08-05

Product Overview

Double-level terminal block

Double-level terminal block, nominal voltage: 500 V, nominal current: 17.5 A, connection type: Quick connect, 1st and 2nd floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.25 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3205118

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626387345

Weight per Piece (excluding packing) 16.570 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 2

Number of connections 4

Potentials 2Nominal cross section 1.5 mm²

Color red

Insulating material PA

Flammability rating according to UL 94 V0

Area of application Machine building

Plant engineering

Process industry

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)

Ambient temperature (actuation) -10 °C ... 90 °C

Maximum load current 17.5 A (with 1.5 mm² conductor cross section)Nominal current I_N 17.5 ANominal voltage U_N 500 V

Open side panel Yes

Dimensions

Width 5.2 mm

End cover width 2.2 mm

Length 99.6 mm

Height NS 35/7,5 49.9 mm

Height NS 35/15 57.4 mm

Connection data

Connection method Quick connection

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.25 mm²Conductor cross section solid max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Conductor cross section flexible min. 0.25 mm²Conductor cross section flexible max. 1.5 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 16

Conductor cross section flexible, with ferrule with plastic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QTTCB 1,5 RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.