

INDUSTRIAL COMPONENT DATA

QPD W 4PE2,5 9-16 M25 1,0 EX 1411391 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD W 4PE2,5 9-16 M25 1,0 EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD W 4PE2,5 9-16 M25 1,0 EX
Catalog number	1411391
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-29D87E1D9E
Generated	2026-08-06

Product Overview

Panel feed-through

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1411391

Packing unit 1 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

Catalog page Page 489 (C-2-2017)

GTIN 4046356930055

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85444290

Country of origin PL (Poland)

General

Note Intended for applications in intrinsically safe circuits according to EN 60079-11 and EN 60079-14.

Type QPD 5x2,5

Length of cable 1 m

Color black

Locking type Screw locking
Connection method QUICKON connection
IDC connection
Number of positions 5
Note number of positions 4+PE
Wrench size, union nut 27 mm
Tightening torque, union nut 10 Nm
Tightening torque, counter nut 5 Nm
Wrench size, counter nut 30 mm
Number of connections 10
Conductor cross section flexible min. 1 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section solid min. 1 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 14
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm
Wire insulation material PVC/PE/TPE/rubber
Wire diameter including insulation 2 mm ... 3.8 mm
Position marking 1, 2, 3, N, PE
Ambient conditions
Degree of protection IP66
IP68 (2 m / 24 h)
IP69K
Ambient temperature (operation) -40 °C ... 100 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Temperature when conductor connected -5 °C ... 50 °C
Electrical characteristics
Nominal current IN 20 A
Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD W 4PE2,5 9-16 M25 1,0 EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.