

INDUSTRIAL COMPONENT DATA

QPD W 4PE2,5 6-11 M25 FC EX 1411389 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD W 4PE2,5 6-11 M25 FC EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD W 4PE2,5 6-11 M25 FC EX
Catalog number	1411389
Category	Sensor-actuator connector chassis
Minimum order	25 Pcs
Document ID	EO-79B8355CB6
Generated	2026-08-05

Product Overview

Panel feed-through

QUICKON panel feed-through for the hazardous area, 4+PE-pos., 1.0 mm²... 2.5 mm²/with QUICKON nut, black, for cable diameter 6 mm ... 11 mm, M25 connection thread with 5 slip-on contacts for slip-on sleeves.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Technical dataNotesGeneral Intended for applications in intrinsically safe circuits in accordance with EN 60079-11 and EN 60079-14.

Product propertiesProduct type Panel feed-through

Product family QPD

Type QPD 5x2,5

Number of positions 5

Connection profile 4+PE

Position marking 1, 2, 3, N, PE

Number of connections 10

Coding coded

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Connection dataConnection technology

Connection method On the device side Spade connection

Connection method On the field side IDC connection

Frequency of connections between conductors of the same cross section max. 10

Conductor connectionConductor cross section flexibel 1 mm² ... 2.5 mm²Conductor cross section solid 1 mm² ... 2.5 mm²

Connection cross section AWG 16 ... 14

Tightening torque Union nut 10 Nm

Tightening torque Locking nut 5 Nm

Wrench size Union nut 27 mm

Wrench size Locking nut 30 mm

DimensionsDimensional drawing

Width 34.6 mm

Height 34.6 mm

Length 71.8 mm

Diameter 34.6 mm

Wrench size 27 mm

Wrench size for mounting 27 mm

Dimensions of slip-on connection 4.8 x 0.8 mm

Electrical propertiesRated surge voltage (II/2) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (III/3) 6 kV

Contact resistance < 3 mΩ

Rated voltage (III/3) 60 V

Nominal voltage UN 60 V

Nominal current IN 20 A

Material specificationsMaterial Housing PA

Material Contact surface silver-plated

Flammability rating according to UL 94 V0

Material wire insulation PVC/PE/TPE/rubber

Cable/lineStru...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD W 4PE2,5 6-11 M25 FC EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.