

INDUSTRIAL COMPONENT DATA

QPD T 4PE6,0 3X12-20 GY 1411419 PHOENIX CONTACT T distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD T 4PE6,0 3X12-20 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD T 4PE6,0 3X12-20 GY
Catalog number	1411419
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-AFCCCF7EFB
Generated	2026-08-06

Product Overview

T distributor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1411419

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 189 (NTK-2014)

GTIN 4046356932219

Weight per Piece (excluding packing) 407.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Type T-distributor

Color gray

Locking type Screw locking

Connection method QUICKON connection

IDC connection

Number of positions 5

Note number of positions 4+PE

Wrench size, union nut 30 mm

Tightening torque, union nut 15 Nm

Number of connections 3

Conductor cross section flexible min. 2.5 mm²

Conductor cross section flexible max. 6 mm²

Conductor cross section solid min. 2.5 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section AWG min. 14

Conductor cross section AWG max. 10

Cabel

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm

Wire insulation material PVC/PE/TPE/rubber

Wire diameter including insulation 2.95 mm ... 5 mm

External cable diameter 12 mm ... 20 mm

Position marking 1, 2, L, N, PE

Ambient conditions

Degree of protection IP66

IP68 (2 m / 24 h)

IP69K

Ambient temperature (operation) -40 °C ... 100 °C

Ambient temperature (storage/transport) -40 °C ... 100 °C

Temperature when conductor connected -5 °C ... 50 °C

Electrical characteristics

Nominal current IN 40 A

Rated current 40 A

Rated voltage (III/3) 690 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 8 kV

Rated surge...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD T 4PE6,0 3X12-20 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.