

INDUSTRIAL COMPONENT DATA

QUINT4-PS/1AC/48DC/20 2904612 PHOENIX CONTACT QUINT POWER primary-switched power supply with selectable outp..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/1AC/48DC/20



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT4-PS/1AC/48DC/20
Catalog number	2904612
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-CF48FB73EF
Generated	2026-08-04

Product Overview

QUINT POWER primary-switched power supply with selectable output characteristic curve, SFB (Selective Fuse Breaking) technology and NFC interface, input: single-phase, output: 48 V DC / 20 A

QUINT POWER power supply switched in primary with selectable output characteristic curve, SFB (Selective Fuse Breaking) technology and NFC interface, input: single phase, output: 48 V DC / 20 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

ETIM for 2904612 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

48 V

Max. output current 1 (EF008284)

30 A

Nominal value output voltage 1 (EF009393)

48 V

Nominal value output current 1 (EF009396)

20 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

100 V

Rated supply voltage AC 60 Hz (EF007077)

100 V

Rated supply voltage DC (EF007078)

110 V

Output voltage stabilized (EF003092)

Yes

Power output (EF003034)

960 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Built-in height (EF000332)

130 mm

Direct mounting possible (EF005689)

No

Width (EF000008)

120 mm

Height (EF000040)

130 mm

Depth (EF000049)

140 mm

Suitable for safety functions (EF001597)

Yes

SIL according to IEC 61508 (EF009889)

None

Performance level according to EN ISO 13849-1 (EF007399)

None

Degree of protection (IP) (EF005474)

IP20

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/1AC/48DC/20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.