

**INDUSTRIAL COMPONENT DATA**

# QUINT4-PS/24-48DC/48DC/2/PT 1098676 PHOENIX CONTACT

## DC/DC Switched Primary Converter, QUINT POWER, Rail Moun..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/24-48DC/48DC/2/PT



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | QUINT4-PS/24-48DC/48DC/2/PT |
| Catalog number  | 1098676                     |
| Category        | DC-power supply             |
| Minimum order   | 1 Pcs                       |
| Document ID     | EO-1AA1867518               |
| Generated       | 2026-08-05                  |

### Product Overview

DC/DC Switched Primary Converter, QUINT POWER, Rail Mount, Input: 24 V DC - 48 V DC, Output: 48 V DC / 2 A  
 Primary switched DC/DC converter, QUINT POWER, Rail mount, Push-in connection, input: 24 V DC - 48 V DC, output: 48 V DC / 2 A

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                       |
|--------------|---------------------------------------|
| Catalog path | PHOENIX CONTACT > Power Supplies (PS) |
|--------------|---------------------------------------|

### Additional Product Information

ETIM for 1098676 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

DC

1st secondary output voltage (EF006792)

48 V

Max. output current 1 (EF008284)

4 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

48 V

Nominal value output current 1 (EF009396)

2 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage DC (EF007078)

22 V

Output voltage stabilized (EF003092)

Yes

Power output (EF003034)

96 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Other

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Built-in height (EF000332)

106 mm

Direct mounting possible (EF005689)

No

Width (EF000008)

45 mm

Height (EF000040)

106 mm

Depth (EF000049)

90 mm

Suitable for safety functions (EF001597)

Yes

SIL according to IEC 61508 (EF009889)

None

Performance level according to EN ISO 13849-1 (EF007399)

None

Degree of protection (IP) (EF005474)

IP20

Degree of protection (NEMA) (EF011959)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/24-48DC/48DC/2/PT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.