

INDUSTRIAL COMPONENT DATA

QUINT4-PS/24DC/24DC/10/SC 1046803 PHOENIX CONTACT

Primary-switched QUINT DC/DC converter for DIN rail mounti..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/24DC/24DC/10/SC



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT4-PS/24DC/24DC/10/SC
Catalog number	1046803
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-9AE7581F4C
Generated	2026-08-05

Product Overview

Primary-switched QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, screw connection, input: 24 V DC, output: 24 V DC / 10 A

QUINT Primary Switched DC/DC Converter for Rail Mounting with SFB (Selective Fuse Breaking) Technology, Screw Connection, Input: 24 V DC, Output: 24 V DC/10 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Power Supplies (PS)
--------------	---------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1046803

Packing unit 1 pc

Catalog page Page 291 (C-4-2019)

GTIN 4055626643748

Weight per Piece (excluding packing) 1,040.000 g

Custom tariff number 85044030

Country of origin TH (Thailand)

Drawings

Insulation electric strength

Output data

LED signaling

Signal contacts - signal output Out 2 (configurable)
Signal contacts - remote signal input (configurable)
Signal connection data
Life expectancy (electrolytic capacitors)
General data
Ambient conditions
Conformance/approvals
Environmental Product Compliance
Input data
Input connection data
Output connection data
Signal contacts - signal output Out 1 (configurable)
Signal contacts - signal output relay 13/14 (configurable)
Signal contacts - signal ground SGnd
Reliability
Switching frequency
Power dissipation
Standards
EMC data
Classifications
Drawings
Block diagram
Diagram
Diagram
Diagram
Schematic diagram
Back to top
Input data
Input voltage range 18 V DC ... 32 V AC
Electric strength, max. 35 V DC (60 s)
Typical current consumption 13.8 A (24 V DC)
Mains buffering typ. 11 ms (24 V DC)
Switch-on time < 1 s
Typical response time 300 ms (from SLEEP MODE)
Inrush current limitation typical 1.5 A (after 1 ms)
Inrush current integral (I_2t) < 0.02 A²s
Input fuse 30 A (slow-blow, internal)
Back to top
Insulation electric strength
Insulation voltage input/output 4 kV DC (type test)
2 kV DC (routine test)
Type test (IEC/EN 60950-1) A 2 kV DC
Type test (IEC/EN 60950-1) B 4 kV DC
Type test (IEC/EN 60950-1) C 0.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/24DC/24DC/10/SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.