

INDUSTRIAL COMPONENT DATA

QUINT4-PS/3AC/24DC/40/IOL 1151047 PHOENIX CONTACT QUINT POWER Primary Switching Power Supplies, Screw Connec..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/3AC/24DC/40/IOL



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT4-PS/3AC/24DC/40/IOL
Catalog number	1151047
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-034E854731
Generated	2026-08-06

Product Overview

QUINT POWER Primary Switching Power Supplies, Screw Connection, Rail Mounting, Input: 3 Phase, Output: 24 V DC / 40 A

Primary switched power supplies, QUINT POWER, Screw connection, Rail mount, input: 3 phase, output: 24 V DC / 40 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

ETIM for 1151047 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

24 V

Max. output current 1 (EF008284)

60 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

24 V

Nominal value output current 1 (EF009396)

40 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

400 V

Rated supply voltage AC 60 Hz (EF007077)

400 V

Rated supply voltage DC (EF007078)

260 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

1217 VA

Power output (EF003034)

960 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Built-in height (EF000332)

130 mm

Direct mounting possible (EF005689)

No

Width (EF000008)

120 mm

Height (EF000040)

130 mm

Depth (EF000049)

125 mm

Suitable for safety functions (EF001597)

Yes

SIL according to IEC 61508 (EF009889)

None

Performance level according to EN ISO 13849-1 (EF007399)

None

Degree of protection (IP) (EF005474)

IP20

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/3AC/24DC/40/IOL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.