

INDUSTRIAL COMPONENT DATA

QUINT4-PS/3AC/48DC/20 2904627 PHOENIX CONTACT QUINT POWER switched primary power supply with selectable outp..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/3AC/48DC/20



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT4-PS/3AC/48DC/20
Catalog number	2904627
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-0419FA3756
Generated	2026-08-05

Product Overview

QUINT POWER switched primary power supply with selectable output characteristic curve, SFB (Selective Fuse Breaking) technology and NFC interface, input: three-phase, output: 48 V DC / 20 A

Quint POWER power supply switched in primary with selectable output characteristic curve, SFB (Selective Fuse Breaking) technology and NFC interface, input: three-phase, output: 48 V DC / 20 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

ETIM for 2904627 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC/DC

1st secondary output voltage (EF006792)

48 V

Max. output current 1 (EF008284)

30 A

Nominal value output voltage 1 (EF009393)

48 V

Nominal value output current 1 (EF009396)

20 A
Short-circuit-proof (EF007332)
Yes
Rated supply voltage AC 50 Hz (EF007076)
400 V
Rated supply voltage AC 60 Hz (EF007077)
400 V
Rated supply voltage DC (EF007078)
260 V
Output voltage stabilized (EF003092)
Yes
Power consumption (EF000346)
1217 VA
Power output (EF003034)
960 W
Stabilized (EF005302)
Yes
Type of electric connection (EF003961)
Screw connection
Suitable for rail mounting (EF003972)
Yes
Wall mounting possible (EF003973)
No
Modular version (EF001126)
No
Built-in height (EF000332)
130 mm
Direct mounting possible (EF005689)
No
Width (EF000008)
120 mm
Height (EF000040)
130 mm
Depth (EF000049)
125 mm
Suitable for safety functions (EF001597)
Yes
SIL according to IEC 61508 (EF009889)
None
Performance level according to EN ISO 13849-1 (EF007399)
None
Degree of protection (IP) (EF005474)
IP20
Degree of protection (NEMA) (EF011959)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/3AC/48DC/20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.