

**INDUSTRIAL COMPONENT DATA**

# QUINT4-PS/48DC/48DC/5/PT 2910128 PHOENIX CONTACT

## DC/DC Switched Primary Converter, QUINT POWER, DIN Rail Mou..

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/48DC/48DC/5/PT



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | QUINT4-PS/48DC/48DC/5/PT |
| Catalog number  | 2910128                  |
| Category        | DC-power supply          |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-DC05474641            |
| Generated       | 2026-08-05               |

### Product Overview

DC/DC Switched Primary Converter, QUINT POWER, DIN Rail Mounting, SFB Technology (Selective Fuse Breaking), Input: 48 V DC, Output: 48 V DC / 5 A

Primary Switched DC/DC Converter, Quint, Rail Mount, SFB Technology (Selective Fuse Breaking), Push-in Connection, Input: 48 V DC, Output: 48 V DC / 5 A

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Power Supplies (PS)

### Additional Product Information

ETIM for 2910128 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

DC

1st secondary output voltage (EF006792)

48 V

Max. output current 1 (EF008284)

10 A

Secondary voltage adjustable (EF007002)

Yes

Nominal value output voltage 1 (EF009393)

48 V

Nominal value output current 1 (EF009396)

5 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage DC (EF007078)

29 V

Output voltage stabilized (EF003092)

Yes

Power output (EF003034)

240 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Other

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Built-in height (EF000332)

130 mm

Direct mounting possible (EF005689)

No

Width (EF000008)

50 mm

Height (EF000040)

130 mm

Depth (EF000049)

125 mm

Suitable for safety functions (EF001597)

Yes

SIL according to IEC 61508 (EF009889)

None

Performance level according to EN ISO 13849-1 (EF007399)

None

Degree of protection (IP) (EF005474)

IP20

Degree of protection (NEMA) (EF011959)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/48DC/48DC/5/PT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.